

Parkway Glue Down Collection

| Style | Plank- 7.1"x 48" | Rectangle- 12"x 24" |
|----------------------|--|---|
| Construction | Luxury Vinyl Plank Non-ortho Phthalate | Luxury Vinyl Tile Non-ortho Phthalate |
| Classification | ASTM F1700 Class III, Type B | ASTM F1700 Class III, Type B |
| Total Thickness | 0.080" (2.0 mm) | 0.080" (2.0 mm) |
| Wear Layer Thickness | 12 mil (0.30 mm) | 12 mil (0.30 mm) |
| Wear Layer | Enhanced Urethane | Enhanced Urethane |
| Edge Treatment | Micro-Bevel | Micro-Bevel |
| Sizes | 7.1" x 48" (180.34 x 1219 mm) | 12" x 24" (305 x 610 mm) |
| Colors | 12 each style | 4 each style |
| Packaging | 7.1"x 48" – 21 pcs 50.84 ft ² (4.72 m ²), 40.0 lbs (18 kg) | 12" x 24" - 21 pcs 42.05 ft ² (3.91m ²), 33.1 lbs (15 kg) |
| Installation Method | All arrows in the same direction. Tiles should be installed block or staggered; when quarter turned, arrows should alternate. | |
| Adhesive | Porous & Non-porous Substrates: V-88 Full Spread, Transitional Pressure Sensitive, High Moisture V-95 Full Spread, 2-part Epoxy XpressStep for LVT & Sheet Vinyl Full Coverage Spray Porous Substrates Only: V-82 Full Spread | |

Testing

| | |
|---|--|
| HUD/FHA | Passes |
| ADAG (American Disability Act Guidelines) | Passes |
| Flexibility (ASTM F137) | Passes - 1" Mandrel - No Crack/Break |
| Dimensional Stability (ASTM F2199) | Passes - Max 0.020 in/lin ft |
| Squareness (ASTM F540) | Passes - Max 0.010" |
| Static Load (ASTM F970 mod.) | Passes - 2,000 PSI: Residual Indent ≤ 0.005" |
| Residual Indentation (ASTM F1914) | Passes - < 8% Avg / 10% Single Value |
| Flooring Radiant Panel (ASTM E648) | Passes - Class 1; ≥ 0.45 watts/cm ² |
| Smoke Density (ASTM E662) | Passes - ≤ 450 |
| Slip Resistance (ASTM C1028) | Passes - ≥ 0.5 Leather: 0.6 Rubber |
| Resistance to Light (ASTM F1515) | Passes |
| Chemical Resistance (ASTM F925) | Passes |
| Resistance to Heat (ASTM F1514) | Passes |

Environmental Data

| | |
|----------------------|---|
| Indoor Air Quality | FloorScore Certified; CDPH v1.1-2017 |
| Product Declarations | EPD |
| LEED Scoreboard | May contribute to LEED credits: LEED 2009: IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials – Flooring LEED v4: Building Product Disclosure & Optimization – EPDs; IEQc2 - Low Emitting Materials |
| Manufacturing | Vietnam |

For more information, contact your Mannington on Main representative or visit